



Date: **6-14-23**

This TCP is to scale:

Sign Spacing - 120'

Taper Length - N/A

Buffer Area - N/A

Posted Speed * %	Minimum Sign Spacing * Distance	Minimum Desirable Taper Lengths * ft			Suggested Longitudinal Buffer Space * ft
		10' Offset	11' Offset	12' Offset	
30	120'	150'	165'	180'	90'
35	160'	205'	225'	245'	120'
40	240'	265'	295'	320'	155'
45	320'	450'	495'	540'	195'
50	400'	500'	550'	600'	240'
55	500'	550'	605'	660'	295'
60	600'	600'	660'	720'	350'
65	700'	650'	715'	780'	410'
70	800'	700'	770'	840'	475'
75	900'	750'	825'	900'	540'

DALLAS LITE & BARRICADE
 SINCE 1988
 WWW.DLBINC.NET 1.800.755.5791

TCP DESIGNER:
Chris Duncan
 682-217-3197

Description: **Right Lane Closure**

Job Location: **American Way**

City: **Terrell**

Contractor: **Estrada Concrete**

Contact Name & Phone #: **Marco Flores 972-865-5402**

PAGE: **1**

SPEED LIMIT **30**

This plan is for illustrative purposes only and has been designed to be a representation of the general orientation of the traffic control devices for your project. Dallas Lite & Barricade will not be held liable for any damages, losses, claims or liabilities whatsoever, whether direct or indirect, incidental, special, consequential, damages, that result from or in connection with the use which may be made of, or reliance upon, the information contained on this plan.